


**ELP**


ENGINEERED LIGHTING  
PRODUCTS

## IWS LED SERIES

SURFACE/PENDENT Mount Indirect for  
Vertical Illumination



Wall Washer



*Ideal placement is 24" to 36" from the front edge of fixture to the surface you are lighting, for 8' to 12' ceilings.*

### System

Surface mount indirect LED with asymmetric wash of light to provide vertical illumination in difficult applications such as mirrored surfaces and video conference key speaker where a shielded lamp is critical. The formed reflector provides even, unscalped illumination with no glare.



TYPE:  
CATALOG #:  
JOB:

SURFACE/PENDENT Mount Indirect for  
Vertical Illumination

## Specifications

Surface mount indirect fixture with asymmetric wash of light to provide vertical illumination. Available in 2' and 4' lengths for use with two or four high efficacy, LED modules respectively for a total of 22 or 44 watts. The formed reflector combines white diffuse with high purity aluminum (99.9%) reflector material with 97% reflectance. It is easily removable without tools for access to the driver and wiring. Fixture design provides complete lamp shielding from all angles, and even, unscalloped illumination with no direct glare. Units utilizes Osram PrevaLED® arrays that are 80+ CRI and rated greater than 60,000 hours.

The spot weld construction 5" deep housing is 22 gauge CRS and is post painted with a TGIC polyester powder coat. Cover and knock-outs provide quick wire access to the back of the fixture for through wiring. All fixtures are supplied standard with Luminaire Disconnect.

**Continuous Mount** – If the fixtures are being mounted in a continuous row, add "CC" to the catalog number and provide row configuration, i.e.: (18) 444W1IW-S-CC for (6) 12' rows.

Knock-outs will be provided between continuous fixtures for through wiring.

c/CSA/us Damp Location Listed, IC Rated – Made in the USA

**U.S. Patent #9,726,337**

## Options

Driver 120/277 0-10 volt, Osram OT True 1% Dim (Standard)  
With End Of Life Indicator -EOL  
With Soft Start -SFT  
With Dim To Off -DTO

**For Alternate Dimming:**

3-wire/Digital, Lutron ECO Systems L3D 1% -DM6  
Digital, Lutron LDE 1% -DM8  
LDE Standard Features include Soft-On,  
Fade to Black and Guaranteed 1% Dimming  
Lower Lumen Output (All Driver Options) -LL\*\*\*

Finish White (Standard)  
Anti-Microbial White -MB  
Custom -Custom



Reflector Combo White/Diffuse (Standard) White -W

Wireless Osram Sylvania Connected Lighting  
Module -WLMS\*\*\*


LED **Must Specify \***  
2700K -27K (90+CRI and California Title 24 Compliant)  
3000K -30K  
3500K -35K  
4000K -40K  
5000K -50K\*\*\*

Louver Diffuse Silver Parallel Blade -LV

Mounting Surface J-Box (Standard)  
Canopy w/Stem -CS (FT of Stem)  
ex. 444W1IW-S-CS4  
Continuous Row (see above) -CC



Model No.	A	Lamp	**Fixture Lumens
222W1IW-S-(*K)	24"	(2) 10.8w LEDs	2285
444W1IW-S-(*K)	48"	(4) 10.8w LEDs	4570



\*\*\* Consult Factory.

Note: All LED luminaires are provided standard with dimming and have a 5 year warranty.