




ELP

ENGINEERED LIGHTING
PRODUCTS

LS-EX LED SERIES

RECESSED Exterior or Concrete Pour
Low Level Steplight



*Ideal placement is 8" to 12"
from the bottom edge of
fixture to the ground.*

System

Small, wet location, low level LED steplights. Shallow recess depth (3") allows easy incorporation into exterior walls. Their unique, indirect optical design provides a soft asymmetric wash of light on the walkway while consuming less than 5 watts.



LS-EX LED SERIES

TYPE:
CATALOG #:
JOB:

RECESSED Exterior or Concrete Pour
Low Level Steplight

Specifications

Small, recessed, wet location low level LED steplight for exterior installation. The fixture recess is only 3" deep allowing easy installation into exterior walls. The 2 or 4 watt fixture has a formed diffuse silver reflector of high purity aluminum (99.9%) with a 97% reflectance. The indirect design provides a soft asymmetric wash of light on the walkway. It utilizes Osram HF2 Narrow Stick LED modules that are 85+ CRI and rated 50,000 hour lamp life.



Housing is made of 18 gauge electro-plated galvanized steel, which is post painted with a primer coat of 3M™ Scotchkote™. The fusion bonded epoxy primer protects metal from corrosion. Then the housing is TGIC polyester powder coated, making it suitable for recessed exterior or concrete pour installations. Formed aluminum face plate attaches with screws and recesses into the housing to mount flush with the finish surface. The face plate has a gasketed 1/8" polycarbonate lens.

c/CSA/us Wet Location & Concrete Pour Listed - Made in the USA

Options

- Driver 120/277 volt Electronic
- Finish Black (Standard)
Bronze -BZ
Custom -Custom
- Fixture Electro-Plated Galvanized Steel (Standard)
Stainless Steel -SS
- Reflector Diffuse Silver 97 (Standard)
- Lens Clear Acrylic Full Lens (Standard)
Frosted Acrylic Full Lens -FLF
Clear Acrylic w/ Light Shield -WLC
(Wildlife – Shield w/ Amber Light)
- LED **Must Specify ***
2700K -27K
3000K -30K
3500K -35K
4000K -40K

Note: All LED luminaires are provided standard with driver with -20° starting and have a 5 year warranty.



Model No.	Lamp	Fixture Lumens
12W1LS-EX-(*K)	2w LEDs	47
14W1LS-EX-(*K)	4w LEDs	93

