

INSTALLATION INSTRUCTIONS

**SC SERIES
WALL WASH
Surface Mount**


The ideal placement of these fixtures would be between 24" and 36" from the surface being lighted to the front edge of the fixture.

FOR SUPPLY CONNECTIONS ENTERING THIS FIXTURE WITHIN 3 INCHES OF A BALLAST USE WIRE SUITABLE FOR AT LEAST 90° C


*** INSTALLATION TO BE DONE IN ACCORDANCE WITH NEC AND APPLICABLE CODES ***

ALUMINUM REFLECTOR CLEANING: Clean reflector with soap & water or alcohol, i.e. Isopropyl Alcohol or other neutral PH factor solvents. Cleaning material should be non-abrasive. **DO NOT** use Ammonia & alkali solutions.


1. To remove the reflector, push in towards housing on lamp side with your hand.




2. This will dislodge the opposite side of the reflector from the (A) ledge.



3. Pull the reflector out.



4. Now you have access to the ballast.




5. Secure the fixture to the ceiling or wall and make wire connections.

REPLACING THE REFLECTOR SHOULD BE THE LAST STEP AFTER PAINTING AND FINISH WORK

REMOVE THE PROTECTIVE PEEL AND REPLACE REFLECTOR.

6. Place the lamp side of reflector on (B) ledge and squeeze reflector back into housing.



7. Push the reflector into (B) ledge.

